


UX-DOWNLIGHT 204

2x18W, TC-D, MB B2,9003

Order code: DAC441321832000



Gross weight	1.70 kg
LOR	36 %
LLPW	23.80 lm/w
Pallette quantity	150 pc

Lighting fixtures Downlights are suitable especially for mounting into different kinds of ceiling boards. The Downlights are best suited to office, classroom, sales areas, showrooms, presentation of merchandise, public buildings, banks, museums, hotels, exhibition halls, entrance areas, decorative entrance areas, foyers, corridors, staircases, conference rooms, etc.

CONSTRUCTION

Housing: galvanized sheet
 Reflectors: aluminium reflector with polished surface
 finish
 Ring: sheet steel, electrostatic powder coat finish RAL 9003 (signal white), other finish types – RAL 9006 (white aluminium), chrome or brass available on request
 Ballast box: galvanized sheet steel, holders to prevent conductors from loosening off the terminal box, two rubber reducing adapters for conductors (through mounting possible)
 Ceiling attachment of the luminaire is done using two metal springs, adjustable for various ceiling widths. The louvre is attached to the luminaire using three springs allowing fast and tool-free light source replacement.

ELECTRICAL COMPONENTS

Luminaires can be equipped with conventional control gear (EEI=B2, standardly not compensated), electronic (EEI=A2) or dimmable electronic control gears (EEI=A1, 1-10V, switch DIM, DALI)

Light sources shall be ordered separately

ACCESSORIES

- an independent metal box for separate placement of the ballast apart from the luminaire (separate gear box version)
- on request, they can be delivered with one or two connectors allowing fast electrical connection: 3-pole connectors Wieland gesis GST 18i3, Wago Winsta 770, AAG Stucchi 1601A/1602A

	OPTIC TURBO LOUVRE	POWER	LAMP	DIMENSIONS		H1	H2	A1	OPENING Ø1	EMERGENCY			
				D1	D2					1H	3H		
UX-Downlight 204	*	1x13	TC-D, TC-DEL	195	155	305	212	120	64	152	175	*	*
UX-Downlight 204	*	1x18	TC-D, TC-DEL	195	155	305	212	120	64	152	175	*	*
UX-Downlight 204	*	1x26	TC-D, TC-DEL	195	155	305	212	120	64	152	175	*	*
UX-Downlight 204	*	2x13	TC-D, TC-DEL	195	155	305	212	120	64	152	175	*	*
UX-Downlight 204	*	2x18	TC-D, TC-DEL	195	155	305	212	120	64	152	175	*	*
UX-Downlight 204	*	2x26	TC-D, TC-DEL	195	155	305	212	120	64	152	175	*	*
UX-Downlight 214	*	1x18	TC-D, TC-DEL	230	196	359	250	145	89	172	205	*	*
UX-Downlight 214	*	1x26	TC-D, TC-DEL	230	196	359	250	145	89	172	205	*	*
UX-Downlight 214	*	2x18	TC-D, TC-DEL	230	196	359	250	145	89	172	205	*	*
UX-Downlight 214	*	2x26	TC-D, TC-DEL	230	196	359	250	145	89	172	205	*	*
UX-Downlight 224	*	1x18	TC-D, TC-DEL	267	228	390	225	160	104	172	240	*	*
UX-Downlight 224	*	1x26	TC-D, TC-DEL	267	228	390	225	160	104	172	240	*	*
UX-Downlight 224	*	1x32	TC-TEL	267	228	390	225	160	104	172	240	*	*
UX-Downlight 224	*	1x42	TC-TEL	267	228	390	225	160	104	172	240	*	*
UX-Downlight 224	*	2x18	TC-D, TC-DEL	267	228	390	225	160	104	172	240	*	*
UX-Downlight 224	*	2x26	TC-D, TC-DEL	267	228	390	225	160	104	172	240	*	*
UX-Downlight 224	*	2x32	TC-TEL	267	228	390	225	160	104	172	240	*	*

